toptech plus 45/45W











the advanced range

Intelligent tech. Sustainable power.

TopTech Plus is the consistent evolution of the proven TopTech range - offering noticeable improvements in performance, user comfort, and sustainability.

This product range combines advanced technology with high efficiency, providing a reliable and powerful solution for professional users. TopTech Plus stands for a well-balanced combination of quality, functionality, and intuitive operation

- making it the smart choice for modern kitchens that value performance without compromise.



toptouch Interface



The new TopTouch user interface offers 23 selectable programs for maximum flexibility and features an intuitive configuration concept.

Frequently used settings can be accessed quickly via the favorites screen function.

The clear graphical display shows the progress of the wash cycle, while extensive customization options allow for full personalization.

With a practical screen lock function, integrated Wi-Fi, and a TFT touchscreen with RGB button, you're always in full control.

Point monitors the machine status through color-coded LEDs, and the robust, scratch-resistant synthetic glass front panel combines durability with elegant design.

	gent Functions & nced Technologies	45- 33 D	45- 33 TD	45W- 33 D
<u></u>	DuoFlow - Proven Pump System – More Efficiency, Less Noise	•	•	•
(1)	QuickReady - Energy management system for reduced heat-up time and a faster start-up process.	•	•	•
	HotWash - Constant heat for faster washing and drying times.	•	•	•
	ProRinse - Constant water pressure for perfect wash results.	•	•	•
1	ThermoStop - Constant Wash Temperature for Maximum Hygiene.	•	•	•
	EvoLution ₃ - Clean Water for Better Washing Results	•	•	•
	ProDrain₄ - Optimized Filtration for Maximum Efficiency.	•	•	•
	UltraRinse ₃ - Perfect wash results with minimal water consumption.	•	•	•
	EnergySaving - Optimized Energy Usage	•	•	•
	HiTech - Innovative wash arm for maximum performance.	•	•	•
	Access - Maintenance Made Easy	•	•	•
@	Inspect - Clear View for Maximum Hygiene	•	•	•
(SmartClean - Self-Cleaning Design for Effortless Operation	•	•	•
THE STATE OF THE S	ProSoft - Gentle Wash Start for Maximum Care	•	•	•
	WaterMaster - Glasswasher Machines with Integrated Reverse Osmosis System			•
	ProDose - Precise dosing for optimal wash results.	•	•	•
(MultiPower - Flexible Power Adaptation for Maximum Compatibility	•	•	•
	CareFree - Continuous water softening for maximum protection.		•	

Dimensions and Weights		45	45W	
Installation size (W x D x H)	mm	600 x 610 x 720	600 x 610 x 820	
Rack size	mm	500 x 500		
Loading height	mm	300		
Maximum plate diameter	mm	285		
Maximum glass height	mm	275		
Compatible with GN 1/1 containers		no		
Compatible with 60 x 40 boxes or trays		no		
Gross weight / Net weight	kg	61 / 55	75 / 69	
Packaging dimensions (W \times D \times H)	mm	690 x 670 x 880	690 x 670 x 880	
Volume (packaged)	m³	0,41	0,41	

Essential Information		45- 45- 45W- 33 D 33 TD 33 D		
Theoretical capacity*		48		
Waterconsumption / rack**		1,5		
Connected load (standard)	W	7.500		
Electrical connection (standard)	V	400/50/3N		
Fuse protection (standard)	amp	16		
Connected load (MultiPower 1)	W	5.500		
Electrical connection (MultiPower 1)	V	400/50/3N		
Fuse protection (MultiPower 1)	amp	16		
Connected load (MultiPower 2 & 3)	W	5.500 / 3.500		
Electrical connection (MultiPower 2 & 3)	V	230/50/3N 230/50/1N		
Fuse protection (MultiPower 2 & 3)	amp	16 / 16		
Inlet water flow pressure min. – max.	bar	0,5 - 6,0		
Inlet water temperature min. – max.	°C	50 - 60 15 - 25		

^{*}Calculated based on standard program 75"

^{**}Calculated based on wash program PR2

Tech Specs		
Tank volume		15
Boiler volume		6
Tank heating		2.000
Boiler heating		5.000
Wash pump	W	500
Rinse pump		200
Drain pump		40
Heat emission latent / sensible		0,4 / 0,3
Steam output		0,6
Noise level		59
Water connection		3/4"
Drain hose // inner / outer Ø		2.000 // 18/24
Detergent / rinse aid hose		1.900 / 1.900

 $^{\star}\text{Techical}$ data is non-binding - valid only as of the specified date and time: 10.06.2025 - 14:40.









EUROTEC s.r.l divisione COLGED Via Romana 6 55011 Altopascio (LU) ITALY www.colged.it

EUROTEC S.R.L.

Viale Europa 24 -

37045 San Pietro di Legnago (VR) Italy

CAP.SOC. Euro 6.456.000,00 I.V. – REG.IMP.VR NR 32820/2015 . R.E.A. VR-281824 –

P.IVA-C.F. – VAT IT 12073160157

GM: Cristina Antoniazzi