











the advanced range

Intelligent tech. Sustainable power.

TopTech Plus is the consistent evolution of the proven TopTech range - offering noticeable improvements in performance, user comfort, and sustainability.

This product range combines advanced technology with high efficiency, providing a reliable and powerful solution for professional users. TopTech Plus stands for a well-balanced combination of quality, functionality, and intuitive operation

- making it the smart choice for modern kitchens that value performance without compromise.



toptouch Interface



The new TopTouch user interface offers 23 selectable programs for maximum flexibility and features an intuitive configuration concept.

Frequently used settings can be accessed quickly via the favorites screen function. The clear graphical display shows the progress of the wash cycle, while extensive customization options allow for full personalization.

With a practical screen lock function, integrated Wi-Fi, and a TFT touchscreen with RGB button, you're always in full control.

Point monitors the machine status through color-coded LEDs, and the robust, scratch-resistant synthetic glass front panel combines durability with elegant design.

Essential Information		
Theoretical capacity*	racks/h	60
Waterconsumption / rack**	I	1,8
Connected load (standard)	W	9.700
Electrical connection (standard)	V	400/50/3N
Fuse protection (standard)	amp	16
Connected load (MultiPower 1)	W	7.700
Electrical connection (MultiPower 1)	V	400/50/3N
Fuse protection (MultiPower 1)	amp	16
Inlet water flow pressure min. – max.	bar	0,5 - 6,0
Inlet water temperature min. – max.	°C	15 - 60

^{*}Calculated based on standard program 60"

	gent Functions & noed Technologies	46L- 33 D	47L- 33 D
@	DuoFlow - Proven Pump System – More Efficiency, Less Noise	•	•
(1)	QuickReady - Energy management system for reduced heat-up time and a faster start-up process.	•	•
	HotWash - Constant heat for faster washing and drying times.	•	•
	ProRinse - Constant water pressure for perfect wash results.	•	•
	ThermoStop - Constant Wash Temperature for Maximum Hygiene.	•	•
	EvoLution₃ - Clean Water for Better Washing Results	•	•
	ProDrain₄ - Optimized Filtration for Maximum Efficiency.	•	•
	UltraRinse ₃ - Perfect wash results with minimal water consumption.	•	•
	EnergySaving - Optimized Energy Usage	•	•
	HiTech - Innovative wash arm for maximum performance.	•	•
	Access - Maintenance Made Easy	•	•
(SmartClean - Self-Cleaning Design for Effortless Operation	•	•
Constitution of the second	ProSoft - Gentle Wash Start for Maximum Care	•	•
	ProDose - Precise dosing for optimal wash results.	•	•
(#)	MultiPower - Flexible Power Adaptation for Maximum Compatibility	•	•

Tech Specs		
Tank volume	I	23
Boiler volume	1	6
Tank heating	W	2.000
Boiler heating	W	7.000
Wash pump	W	700
Rinse pump	W	200
Drain pump	W	40
Heat emission latent / sensible	kW	0,5 / 0,3
Steam output	kg/h	0,8
Noise level	dB	59
Water connection		3/4"
Drain hose // inner / outer Ø	mm	2.000 // 18/24
Detergent / rinse aid hose	mm	1.800 / 1.800
*Tachical data is non hinding until only so of the anastis	-1	

^{*}Techical data is non-binding - valid only as of the specified date and time: 01.07.2025 - 10:15.









Dimensions and Weights		46L	47L	
Installation size (W x D x H)	mm	600 x 700 x 852	600 x 700 x 1225	
Rack size	mm	500 x 600		
Loading height	mm	400		
Maximum plate diameter	mm	390		
Maximum glass height	mm	375		
Compatible with GN 1/1 containers		yes		
Compatible with 60 x 40 boxes or trays		yes		
Gross weight / Net weight	kg	70 / 64	88 / 82	
Packaging dimensions (W \times D \times H)	mm	670 x 780 x 980	670 x 780 x 1250	
Volume (packaged)	m³	0,52	0,65	

EUROTEC s.r.l divisione COLGED Via Romana 6 55011 Altopascio (LU) ITALY www.colged.it

EUROTEC S.R.L.

Viale Europa 24 –

37045 San Pietro di Legnago (VR) Italy

CAP.SOC. Euro 6.456.000,00 I.V. – RÉG.IMP.VR NR 32820/2015 . R.E.A. VR-281824 – P.IVA-C.F. – VAT IT 12073160157

GM: Cristina Antoniazzi

^{**}Calculated based on wash program PR2