

toptechplus 46L-33D

COLGED
useful innovation

Code commercial

Code production

46L23D

919533



	Overall dimension (WxDxH)	mm	575x700x850
	Packaging dimension (WxDxH)	mm	690x670x980
	Gross weight	Kg	66
	Net weight	Kg	91
	Volume	mc	0,52
	Rack size	mm	500x600
	Max door\hood opening	mm	405
	Max glasses\plate height	mm	380
	Flank's construction		double wall
	Tank construction		deep drawn
	Tank volume		23
	Tank heating element	W	2000
	Tank surface strainers		inox
	Wash arms		parallel clip-in
	Wash pump type		double flow
	Wash pump power	W	700
	Wash temperature	°C	55
	Boiler type		open
	Boiler volume		6
	Back-flow system		break tank
	Boiler heating element		7000
	Rinse booster pump		yes
	Rinse booster pump power	W	200
	Rinse temperature	°C	45
	Rinse arms		parallel clip-in
	Drain system		partial drain
	Drain filter		triple filter
	Drain pump		yes
	Rinse aid dispenser	peristaltic	yes
	Detergent dispenser	peristaltic	yes
	Rinse water consumption	liter/rack	1,8
	Optimal external water pressure	bar	0,5-6,0
	Wash cycle (P)	sec	40
	Fast program (DIN)		80
	Total programs	programs	n°23
	Electric connection	V-PH-HZ	400V 3N 50Hz
	Total power	W	9.700
	Alternative power	W	7.700
	Fuse	A	16
	Water softener		no



Equipments

Flat rack	n°1	780148
Plate rack	n°1	708180
Cutterly rack	n°1	780139
Electric cable	n°1	yes
Drain hose	n°1	yes
Fill hose	n°1	yes

toptechplus 46L-33D

