

top tech **plus**  **48 NRG** steam



the advanced range

Intelligent tech. Sustainable power.

TopTech Plus is the consistent evolution of the proven TopTech range - offering noticeable improvements in performance, user comfort, and sustainability.


This product range combines advanced technology with high efficiency, providing a reliable and powerful solution for professional users. TopTech Plus stands for a well-balanced combination of quality, functionality, and intuitive operation

– making it the smart choice for modern kitchens that value performance without compromise.

COLGED
useful innovation

www.colged.it

toptouch Interface



The new **TopTouch** user interface offers 23 selectable programs for maximum flexibility and features an intuitive configuration concept.

Frequently used settings can be accessed quickly via the favorites screen function. The clear graphical display shows the progress of the wash cycle, while extensive customization options allow for full personalization.

With a practical screen lock function, integrated Wi-Fi, and a TFT touchscreen with RGB button, you're always in full control.

Point monitors the machine status through color-coded LEDs, and the robust, scratch-resistant synthetic glass front panel combines durability with elegant design.

Intelligent Functions & Advanced Technologies	48-33 D NRGsteam	48-33 TD NRGsteam
DuoFlow - Proven Pump System – More Efficiency, Less Noise	■	■
QuickReady - Energy management system for reduced heat-up time and a faster start-up process.	■	■
HotWash - Constant heat for faster washing and drying times.	■	■
ProRinse - Constant water pressure for perfect wash results.	■	■
ThermoStop - Constant Wash Temperature for Maximum Hygiene.	■	■
EvoLution3 - Clean Water for Better Washing Results	■	■
ProDrain4 - Optimized Filtration for Maximum Efficiency.	■	■
UltraRinse3 - Perfect wash results with minimal water consumption.	■	■
EnergySaving - Optimized Energy Usage	■	■
HiTech - Innovative wash arm for maximum performance.	■	■
NRGsteam - Sustainable Heat Recovery for Professionals	■	■
Inspect - Clear View for Maximum Hygiene	■	■
Access - Maintenance Made Easy	■	■
SmartClean - Self-Cleaning Design for Effortless Operation	■	■
ProSoft - Gentle Wash Start for Maximum Care	■	■
ProDose - Precise dosing for optimal wash results.	■	■
MultiPower - Flexible Power Adaptation for Maximum Compatibility	■	■
CareFree - Continuous water softening for maximum protection.		■

Dimensions and Weights		
Installation size (W x D x H)	mm	633 x 750 x 2283
Overall Dimensions (W x D x H)	mm	724 x 812 x 2283
Rack size	mm	500 x 500
Loading height	mm	470
Maximum plate diameter	mm	450
Maximum glass height	mm	450
Compatible with GN 1/1 containers		yes
Compatible with 60 x 40 boxes or trays		no
Gross weight / Net weight	kg	115 + 25 / 105 + 20
Packaging dimensions (W x D x H)	mm	870 x 760 x 1540 + 720 x 750 x 300
Volume (packaged)	m³	1,02 + 0,15

Essential Information		
Theoretical capacity*	racks/h	60
Waterconsumption / rack**	l	1,5
Waterconsumption / rack***	l	1,4
Connected load (standard)	W	10.200
Electrical connection (standard)	V	400/50/3N
Fuse protection (standard)	amp	16
Connected load (MultiPower)	W	7.700
Electrical connection (MultiPower)	V	400/50/3N
Fuse protection (MultiPower)	amp	16
Inlet water flow pressure min. – max.	bar	0,5 - 6,0
Inlet water temperature min. – max.	°C	15 - 25


*Calculated based on standard program 60"

**Calculated based on wash program PR2

*** For further details, please refer to the table "Standard EN IEC 63136:2019."

Tech Specs		
Tank volume	l	20
Boiler volume	l	7
Tank heating	W	2.500
Boiler heating	W	7.000
Wash pump	W	700
Rinse pump	W	200
Drain pump	W	40
Heat emission latent / sensible	kW	0,5 / 0,6
Steam output	kg/h	0,7
Noise level	dB	59
Water connection		3/4"
Drain hose // inner / outer Ø	mm	1.700 // 33/43
Detergent / rinse aid hose	mm	2.500 / 2.500

*Technical data is non-binding - valid only as of the specified date and time: 05.05.2025 - 09:29.



EUROTEC s.r.l divisione COLGED
Via Romana 6
55011 Altopascio (LU)
ITALY
www.colged.it

EUROTEC S.R.L.
Viale Europa 24 –
37045 San Pietro di Legnago (VR) Italy
CAP.SOC. Euro 6.456.000,00 I.V. – REG.IMP.VR NR 32820/2015 . R.E.A. VR-281824 –
P.IVA-C.F. – VAT IT 12073160157
GM: Cristina Antoniazzi