











## the advanced range

Intelligent tech. Sustainable power.

TopTech Plus is the consistent evolution of the proven TopTech range - offering noticeable improvements in performance, user comfort, and sustainability.

This product range combines advanced technology with high efficiency, providing a reliable and powerful solution for professional users. TopTech Plus stands for a well-balanced combination of quality, functionality, and intuitive operation

- making it the smart choice for modern kitchens that value performance without compromise.



## toptouch Interface



The new **TopTouch** user interface offers 23 selectable programs for maximum flexibility and features an intuitive configuration concept.

Frequently used settings can be accessed quickly via the favorites screen function.

The clear graphical display shows the progress of the wash cycle, while extensive customization options allow for full personalization.

With a practical screen lock function, integrated Wi-Fi, and a TFT touchscreen with RGB button, you're always in full control.

Point monitors the machine status through color-coded LEDs, and the robust, scratch-resistant synthetic glass front panel combines durability with elegant design.

	ent Functions & nced Technologies	48 -33 D	48 -33 TD	48 -33 DL
@	<b>DuoFlow</b> - Proven Pump System  – More Efficiency, Less Noise	•	•	•
$\overline{4}$	<b>QuickReady</b> - Energy management system for reduced heat-up time and a faster start-up process.	•	•	•
	<b>HotWash</b> - Constant heat for faster washing and drying times.	•	•	•
	<b>ProRinse</b> - Constant water pressure for perfect wash results.	•	•	•
	<b>ThermoStop</b> - Constant Wash Temperature for Maximum Hygiene.	•	•	•
	<b>EvoLution<sub>3</sub></b> - Clean Water for Better Washing Results	•	•	•
	<b>ProDrain<sub>4</sub></b> - Optimized Filtration for Maximum Efficiency.	•	•	•
	<b>UltraRinse</b> <sub>3</sub> - Perfect wash results with minimal water consumption.	•	•	•
	EnergySaving - Optimized Energy Usage	•	•	•
	<b>HiTech</b> - Innovative wash arm for maximum performance.	•	•	•
	<b>ProLift</b> - Automatic Hood Opening for Effortless Comfort			•
<b>@</b>	Inspect - Clear View for Maximum Hygiene	•	•	•
	Access - Maintenance Made Easy	•	•	•
<b>(</b>	<b>SmartClean</b> - Self-Cleaning Design for Effortless Operation	•	•	•
THE THE PARTY OF T	<b>ProSoft</b> - Gentle Wash Start for Maximum Care	•	•	•
	<b>ProDose</b> - Precise dosing for optimal wash results.	•	•	•
<b>\rightarrow</b>	<b>MultiPower</b> - Flexible Power Adaptation for Maximum Compatibility	•	•	•
	<b>CareFree</b> - Continuous water softening for maximum protection.		•	

Essential Information		
Theoretical capacity*		60
Waterconsumption / rack**		1,5
Waterconsumption / rack***		1,5
Connected load (standard)	W	10.200
Electrical connection (standard)	V	400/50/3N
Fuse protection (standard)	amp	16
Connected load (MultiPower)		7.700
Electrical connection (MultiPower)		400/50/3N
Fuse protection (MultiPower)		16
Inlet water flow pressure min. – max.		0,5 - 6,0
Inlet water temperature min. – max.		15 - 60

<sup>\*</sup>Calculated based on standard program 60"


 $<sup>^{\</sup>star\star\star}$  For further details, please refer to the table "Standard EN IEC 63136:2019."

Tools Chaos		_			
Tech Specs					
Tank volume		20			
Boiler volume		7			
Tank heating		2.500			
Boiler heating		7.000			
Wash pump	W	700			
Rinse pump		200			
Drain pump		40			
Heat emission latent / sensible		1,1 / 0,6			
Steam output		1,6			
Noise level		59			
Water connection		3/4"			
Drain hose // inner / outer Ø		1.700 // 33/43			
Detergent / rinse aid hose		2.500 / 2.500			

<sup>\*</sup>Techical data is non-binding - valid only as of the specified date and time: 04.04.2025 - 11:15.









Dimensions and Weights		
Installation size (W x D x H)		633 x 750 x 1590
Overall Dimensions (W x D x H)		724 x 812 x 1590
Rack size		500 x 500
Loading height	mm	470
Maximum plate diameter		450
Maximum glass height		450
Compatible with GN 1/1 containers		yes
Compatible with 60 x 40 boxes or trays		no
Gross weight / Net weight		115 / 105
Packaging dimensions (W $\times$ D $\times$ H)		870 x 760 x 1540
Volume (packaged)		1,02

EUROTEC s.r.l divisione COLGED Via Romana 6 55011 Altopascio (LU) ITALY www.colged.it

EUROTEC S.R.L.

Viale Europa 24 –

37045 San Pietro di Legnago (VR) Italy

CAP.SOC. Euro 6.456.000,00 İ.V. – REG.IMP.VR NR 32820/2015 . R.E.A. VR-281824 – P.IVA-C.F. – VAT IT 12073160157

GM: Cristina Antoniazzi

<sup>\*\*</sup>Calculated based on wash program PR2